

# Crash Test Barrier

# WG11 Frontal Offset Deformable Barrier

## for Frontal Crashworthiness Evaluation

#### Description


The Plascore Frontal Offset Barrier is used for full scale crash testing in the automotive safety field. Barrier performance is intended to provide a measurement tool with sufficient precision to ensure repetitive and correlative results that reflects the protective performance of a motor vehicle with respect to occupants.

#### Construction

- Main Body Core 1.8-3/4-P-3003
- Bumper Core 5.2-1/4-P-3003
- Base Plate 2.0mm 5052 H32
- Main Cladding 0.8mm 5052 H34
- Bumper Cladding 0.8mm 5052 H34


### **Specifications**

United Nations ECE R94 European Directive 96/79/EC NHTSA Lab Test Procedure Dynamic Side Impact Protection TP214D Appendix C



# **Crush Properties**





Bumper Deformable Core



Displacement (mm)

## Availability

Plascore Item B104940

Available from distribution locations worldwide.

Includes Certificate of Conformance and Test Data.

Paint: Grey or Blue anti-reflective paint standard. Custom paint

configurations available.

Packaging: Individual cardboard container 1075mm X 825mm X 580mm

Packaged Weight: 25kg



Plascore, Inc., employs a quality management system that is Nadcap, AS9100, ISO 9001 and ISO 14001 certified.

IMPORTANT NOTICE: The information contained in these materials regarding Plascore's products, processes, or equipment, is intended to be up to date, accurate, and complete. However, Plascore cannot warrant that this is always the case. Accordingly, it is a purchaser's or user's responsibility to perform sufficient testing and evaluation to determine the suitability of Plascore's products for a particular purpose. Information in these materials and product specifications does not constitute an offer to sell. Your submission of an order to Plascore constitutes an offer to purchase which, if accepted by Plascore, shall be subject to Plascore's terms and conditions of sale. PLASCORE MAKES NO WARRANTIES OF ANY KIND REGARDING THESE MATERIALS OR INFORMATION, EITHER EXPRESS OR IMPLIED, INCLUDING WITHOUT LIMITATION THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Plascore owns and shall retain all worldwide rights in its intellectual property, and any other trademarks used in these materials are the property of their respective owners. The information in these materials shall not be construed as an inducement, permission, or recommendation to infringe any patent or other intellectual property rights of any third parties.



#### **Corporate Headquarters**

# Plascore Incorporated 615 N. Fairview St.

Zeeland, MI 49464-0170

Web

Phone (616) 772-1220
Toll Free (800) 630-9257
Fax (616) 772-1289
Email sales@plascore.com

www.plascore.com

#### Europe

#### Plascore GmbH&CoKG

Feldborn 6

D-55444 Waldlaubersheim Germany

Phone +49(0) 6707-9143 0 Fax +49(0) 6707-9143 40 Email sales.europe@plascore.de Web www.plascore.de